

Gear Oil Stop Leak (GOSL)

Gear Oil Stop Leak

Product properties

Gear Oil Stop Leak reliably stops the oil loss on the seals of manual gearboxes. Protects gearbox against lack of lubrication and damage due to oil loss. Reduces wear and tear and ensures optimum lubrication. Maintains seals, O-rings and shaft-seals and keeps them supple. Reduces the oxidation of transmission oils.

Area of application

In all manual gearboxes, secondary and differential transmissions. **Do not use in automatic transmissions and gearboxes with wet clutches.**

Application

Add to the gear oil. Use with every oil change or the used oil (observe the maximum filling quantity, reduce the oil quantity if necessary). The product is miscible with all commercially available oils. Observe the mixing ratio!

Consumption

50 ml for 2-3 ltr. gear oil. Mixing Ratio 1:60

Reaction time

Works during running.

Technical data

Physical state: viscous

Colour: brown

Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.89 - 0.92 g/cm³

Water resistant

Available sizes	Item no.	PU
50ml	P2141	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.